



Piezometers and filter

Technical Features

Piezometers are PVC pipes, they can be joined by couplers or M/F thread, they are available closed or micro-slotted.

Casagrande filter can have 2 x 1/2" thread or 1 x 1/2" and 1 x 1 1/2" (to insert inside an OG200R electrical piezometer)

Applications

Piezometers are installed where it is necessary to monitor the level of the water underground and the pore pressure:


- Automatic or manual measure of ground-water;
- Pore pressure measure;

Related Instrumentation

- Water Level Indicators OG10/OG15
- Electrical Piezometers OG200R;
- Datalogger D200-D800;
- OtrMonitoring

Features

- Material PVC;
- Diameters 1/2" - 1" 1/2 - 2";
- Length 3000 mm.



Technical Specification

Casagrande Filter 1/2", 1/2"	Ø max 60 mm L 265 mm
Casagrande Filter 1/2", 1" 1/2	Ø max 79 mm L 290 mm
1/2" Casing	Ø Ext 21 mm, Ø Int 16 mm, 3 m bars
1" 1/2 Casing	Ø Ext 48 mm, Ø Int 40 mm, 3 m bars

Codes & Part Numbers

P/N 2022000 Casagrande Filter 1/2", 1/2"
 P/N 2022001 Casagrande Filter 1/2", 1" 1/2
 P/N 2022002 1/2" Casing
 P/N 2022003 1" 1/2 Casing

